

Product Number: 5150B

Color	Black	
Material Thickness (no liner)	0.060 in. (1.5mm)	ASTM D-3652
Tolerance	+/- 10%	
Standard Length*	36 yds. (108 ft.) [33M]	
Standard Log Width**	17.5 in. (450mm)	
Carrier	Acrylic Foam	
Liner	Red Siliconized PE: 0.005" (0.13mm)	
Core	White Plastic: 3 in. ID (76.2mm) 3.25 in. OD (82.55mm)	




Double Sided Acrylic Foam Tapes

Superior Quality and Adhesive Bonding Power

Extreme Bond® 5150B is a black 60mil thick double sided closed cell pressure sensitive acrylic foam tape. The 5150B also offers an extremely powerful longterm holding capability, resists UV light, extreme temperatures & offers weather sealing abilities. The 5150B is often used in the Automotive Aftermarket Industry as well as a wide variety of applications.

Material Structure



90° Adhesion:

Test Method: ASTM D-3330

Substrate Tested: Stainless Steel
Speed / Load: 12 inch per/minute
Tape Width: 1 inch
Test Result: 22 lbs. per/inch

Dynamic Shear:

Test Method: ASTM D-1002

- 20min = 115.2 lbf/in².
- 24 hours = 115.2 lbf/in²
- 48 hours = 116.6 lbf/in²
- 250 hours @ 100% RH = 119.5 lbf/in²
- 250 hours @ 176°F = 120.9 lbf/in.
- 250 hours @ -4°F = 112.4 lbf/in.

Static Shear:

Test Methods: ASTM D3654
(Stainless Steel)

- (1.2677 in² overlap, held for 7 days)
- 73.4°F @ 3.3 lbs. = Passed
 - 199.4°F @ 1.1 lb. = Passed

Temperature Resistance: 248°F

Tensile Strength: 90 lb/in² Test Method: ASTM D-897

Minimum Shelf Life: 12 months from the delivery date
(When stored in the original carton at 21°C (70°F) & 50% Relative Humidity.)

All products distributed by H&K Supplies, Inc. are guaranteed to be free from defect at the time of shipping when tested, according to H&K Supplies product specifications. The performance of the tape depends on many factors, but isn't limited to, the materials upon which the tape is being adhered to and the preparation of those materials. For the best performance use the manufacture's guidelines listed under "Application Guide" on our website, www.hksuppliesinc.com. The above figures are average values, established to our best knowledge and experience, but we recommend that you carry out your own tests to determine the suitability of specification purpose.

* Available in longer lengths

** Available in larger widths

Please contact your Sales Representative for further details.

